

# GLOBESTAR WT



## TECHNICAL DATA

Tire Size	Rim Size	Clip on	Profile	Tire dimensions		Tire dimensions		Tread Width	Other Vehicles load capacity (Kg)		Tire load capacity on forklifts at Max. Speed				
				Max width ±1% (mm)	OD ± 2% (mm)	Max width ±1% (inch)	OD ± 2% (Inch)		6 Km/h	10 Km/h	16 Miles/h (Lbs)		25 Km/h (Kg)		
											Load wheel	Steer wheel	Load wheel	Steer wheel	
4.00-4	2.10 -4		GS-WT	99	304	4	12	86	535	485	1180	910	535	412	
4.00-4	2.50 C-4		GS-WT	99	304	4	12	86	535	485	1180	910	535	412	
4.00-8	3.00 D-8		GS-WT	104	403	4	16	96	950	860	2095	1610	950	730	
5.00-8	3.00 D-8	•	GS-WT	116	444	5	17	106	1415	1285	3120	2405	1415	1090	
15x4 1/2-8	125/75-8	3.00 D-8	•	GS-WT	115	374	5	15	106	1040	945	2295	1765	1040	800
16x6-8	150/75-8	4.33 R-8	•	GS-WT	139	406	5	16	135	1495	1360	3210	2535	1495	1150
18x7-8	180/70-8	4.33 R-8	•	GS-WT	152	451	6	18	146	2145	1945	4730	3640	2145	1650
140/55-9		4.00 E-9	•	GS-WT	129	377	5	15	112	1170	1060	2580	1986	1170	900
6.00-9		4.00 E-9	•	GS-WT	139	517	5	20	130	1885	1710	4155	3195	1885	1450
21x8-9	200/75-9	6.00 E-9	•	GS-WT	179	514	7	20	168	2755	2505	6075	4675	2755	2120
6.50-10		5.00 F-10	•	GS-WT	156	563	6	22	142	2340	2125	5160	3970	2340	1800
200/50-10		6.50 F-10	•	GS-WT	191	455	8	18	170	2470	2240	5445	4190	2470	1900
23x9-10	225/75-10	6.50 F-10	•	GS-WT	197	580	8	23	190	3445	3125	7595	5840	3445	2650
7.00-12		5.00 S-12	•	GS-WT	167	645	7	25	155	2920	2645	6435	4940	2920	2240
23x10-12	250/60-12	8.00 G-12	•	GS-WT	234	580	9	23	218	3770	3420	8310	6390	3770	2900
27x10-12	250/75-12	8.00 G-12	•	GS-WT	243	670	10	26	212	3900	3540	8600	6615	3900	3000
7.00-15		5.50-15	•	GS-WT	175	704	7	28	166	3545	3215	7815	6005	3545	2725
7.00-15		6.00-15	•	GS-WT	175	704	7	28	166	3545	3215	7815	6005	3545	2725
8.15-15 (28x9-15)	225/75-15	7.00-15	•	GS-WT	214	680	8	27	195	3770	3420	8310	6390	3770	2900
8.25-15		5.50-15	•	GS-WT	209	806	8	32	190	4750	4300	10470	8045	4750	3650
8.25-15		6.50-15	•	GS-WT	209	806	8	32	190	4750	4300	10470	8045	4750	3650
250-15	250/70-15	7.00-15	•	GS-WT	216	709	9	28	204	4750	4310	10470	8045	4750	3650
250-15	250/70-15	7.50-15	•	GS-WT	216	709	9	28	204	4750	4310	10470	8045	4750	3650
300-15	315/70-15	8.00-15	•	GS-WT	262	811	10	32	255	5850	5310	12895	9920	5850	4500
355/65-15		9.75-15	•	GS-WT	291	819	11	32	273	7800	6430	17190	13230	7800	6000
9.00-20		6.50-10		GS-WT	231	970	9	38	197	5340	5200	11770	9810	5340	4450
9.00-20		7.00-20		GS-WT	231	970	9	38	197	5340	5200	11770	9810	5340	4450
10.00-20		7.00-20		GS-WT	250	1005	10	40	222	6000	5450	13230	11025	6000	5000
10.00-20		7.50-20		GS-WT	250	1005	10	40	222	6000	5450	13230	11025	6000	5000
10.00-20		7.50-20	•	GS-WT	250	1005	10	40	222	6000	5450	13230	11025	6000	5000
10.00-20		8.00-20		GS-WT	250	1005	10	40	222	6000	5450	13230	11025	6000	5000
12.00-20		7.50-20		GS-WT	284	1084	11	43	251	7500	6810	16535	13780	7500	6250
12.00-20		8.00-20		GS-WT	284	1084	11	43	251	7500	6810	16535	13780	7500	6250
12.00-20		8.50-20		GS-WT	284	1084	11	43	251	7500	6810	16535	13780	7500	6250